

# ETS

**Electronic Technical Services Inc.**  
211 Conchas SE  
Albuquerque, NM 87123  
PH 505-888-3923 FAX 505-888-3926  
Website: www.etsnm.com

## Microphones

### Caution

*It is the responsibility of the installation company and end user to comply with state and federal privacy laws regarding the use of audio surveillance equipment. If you are unfamiliar with these laws, consult a qualified attorney. In most cases, posting the provided warning label in plain view is all that is required.*

### SM1 Omni-directional Microphone

*Standard omni-directional microphone. 25' range in all directions. Selectable on/off treble boost circuit enhances time-lapse recordings. Available in white only. Flush or surface mountable.*

- Low noise MOSFET pre-amplifier.
- Adjustable gain.
- Line level unbalanced output.
- Limiter circuit selectable on/off.
- Easy cable run termination.
- Power: 12VDC @ 10mA.



### SM1-SS Omni-Directional Microphone

*Standard omni-directional microphone mounted on a stainless steel plate. 25' range in all directions. Selectable on/off treble boost circuit enhances time-lapse recordings Flush or surface mountable.*

- Low noise MOSFET pre-amplifier.
- Adjustable gain.
- Line level unbalanced output.
- Limiter and TB circuits selectable on/off.
- Easy cable run termination.
- Power: 12VDC @ 10mA.

### SM1-U Unidirectional Microphone

*Uni-directional microphone for use where background noise must be reduced. Simply mount the SM1-U in the direction of interest.*

- Highly reduced sensitivity on all sides.
- Similar in appearance to a fire suppression sprinkler head.
- Excellent ambient noise rejection.
- Low noise MOSFET pre-amplifiers.
- Line level unbalanced output.
- Limiter and TB circuits selectable on/off.
- Easy cable run termination.
- Power: 12VDC @ 10mA.

