



Sound Surveillance™

Electronic Technical Services Inc.
211 Conchas SE
Albuquerque, NM 87123
PH 505-888-3923 FAX 505-888-3926
Website: www.etsnm.com

SMDA-4 4 Channel Distribution Amplifier

Description

Distributes a single SM1 series microphone signal out to four un-balanced line level RCA (or 3.5mm) connectors. Use to send audio from one microphone to 4 locations.



Includes

- SMDA-4 Distribution Amplifier
- 12 VDC AC adapter.
- 4 each 3' RCA or 3.5mm patch cables.
- Installation instructions.

Options

- SPECIFY: RCA OR 3.5mm output connectors.

Wiring Requirements

- Microphone cable run: Stranded 22-gauge, 2-conductor shielded cable. Distances up to 1500 feet.
- Outputs: Audio coaxial cable, 1500 feet max each.

Warranty : 1 year parts and labor.

Made in USA

SMDA-4 Distribution Amplifier Specifications

- Standard RCA or 3.5mm jacks for connection to DVRs etc.
- Line level (0db) output levels.
- Adjustable level control for each output.
- Euro-style connectors makes cable terminations fast and clean.
- LED power indicator.
- Power: 12 VDC @ 60mA
- Reverse polarity protected.
- All power circuitry and cable runs protected with auto-reset type fuse.
- Black plastic ABS housing.
- Dimensions: L 2.7 x W 1.7 x H 1.6

Caution

It is the responsibility of the installation company and end user to comply with state and federal privacy laws regarding the use of audio surveillance equipment. If you are unfamiliar with these laws, consult a qualified attorney. In most cases, posting the provided warning labels in plain view is all that is required.